

MODEL	S10	S15	S20	S25	S30	S35	S40	S45	S50	S75	S100	S150
CAPACITY Lt	100	150	200	250	300	350	400	450	500	750	1000	1500
EMPTY WEIGHT Kg	182	265	280	350	380	400	540	600	700	950	1000	1750
<b>WEIGHT OF CONCRETE *</b>	240	360	480	600	720	840	960	1080	1200	1800	2400	3600
TOTAL WEIGHT LOADED Kg **	422	625	760	950	1100	1240	1500	1680	1900	2750	3400	5350
TYPE OF TRASMISSION	ADAPTOR	ADAPTOR	ADAPTOR	CHAIN	CHAIN	CHAIN	CHAIN	CHAIN	CHAIN	CHAIN	CHAIN	CHAIN+2 MOT
RECOMMENDED RPM	30	30	30	30	30	30	30	30	30	30	30	30
RELATIONSHIP TRASMISSION	1/8,4	1/8,4	1/8,4	10/54	10/54	10/54	9/46	9/46	9/46	10/65	10/65	10/80
OEL FLOW Lt Min / Max	41/75	41/75	41/75	41/75	41/75	52/90	65/90	69/150	69/150	123/240	123/240	160/250
CONSTANT PRESSURE Bar	130	130	130	140	140	180	160	160	160	180	160	180
MAX. PRESSURE Bar	180	180	180	180	180	210	190	190	190	200	190	200
APERTURA SCARICO CENTRALE	IDRAULICA	IDRAULICA	IDRAULICA	IDRAULICA	IDRAULICA	IDRAULICA	IDRAULICA	IDRAULICA	IDRAULICA	IDRAULICA	IDRAULICA	IDRAULICA
DIMENSIONI LaLuXh	100x70x70	100x70x70	125x85x100	155x90x100	160X100X110	170x100x110	165x105x120	173x110x130	195x110x130	205x125x145	220x125x145	215x150x150

<b>S180</b>	<b>S200</b>
1800	2000
1800	1900
4320	4800
6120	6700
CHAIN+2MOT	CHAIN+2MOT
30	30
10/80	10/80
160/250	160/250
180	160
200	190
IDRAULICA	IDRAULICA
235x150x150	260x165x165